



- NOTES:
1. ALL RESISTORS ARE 1/2W, 5% UNLESS OTHERWISE SPECIFIED.
 2. ALL CAPACITORS ARE 50V UNLESS OTHERWISE SPECIFIED.
 3. # DENOTES 20PPM WIRE TEMPERATURE COEFFICIENT
 4. METER SWITCH, S2, AS VIEWED FROM REAR, SHOWN IN VOLTAGE POSITION.
 5. _____ DENOTES VOLTAGE FEEDBACK SIGNAL.
 6. _____ DENOTES VOLTAGE SIGNAL.
 7. TRANSFORMER SHOWN STRAPPED FOR 115V OPERATION.
 8. SEE INSTRUCTION MANUAL FOR 220VAC.
 9. DC VOLTAGES WERE MEASURED UNDER THE FOLLOWING CONDITIONS:
 - A. 115VAC INPUT.
 - B. 115VAC INPUT.
 - C. VOLTAGES REFERENCED TO +5 UNLESS OTHERWISE NOTED.
 - D. ALL READINGS TAKEN IN CONSTANT VOLTAGE OPERATION AT MAXIMUM RATED OUTPUT WITH NO LOAD CONNECTED AND CURRENT CONTROL TURNED FULLY COUNTERWISE.

Figure 7-2. Model 6216A, Schematic Diagram

