

19" ULTRA HIGH RESOLUTION DIGITAL IMAGE DISPLAY

Features

- 2048 x 1536 Pixel Display
- 2048 x 2048 Pixel Frame Buffer
- Scroll and Window Functions
- 16-Bit Parallel Interface operates at up to 20 M byte/sec
- 0.2 Sec Display Update Time
- 256 Levels of Gray-Scale

Typical Applications

- Photogrammetry
- Picture Archiving and Communication Systems
- Reconnaissance
- Gray-scale Imaging
- Computer-aided Publishing

The GMA 251 is a member of the Tektronix display product family, which provides unparalleled raster-scan video performance.

The GMA 251 is especially suited to system builders in the fields of gray-scale imaging, military reconnaissance, PACS, computer-aided publishing, document retrieval, and other similar technical applications.

The GMA 251 makes the benefits of high-resolution video available to the system builder. Key features include a bright, stable, flicker-free 60 Hz refresh rate, a full 1536 vertical by 2048 horizontal viewable pixels, and a crisp, well-focused beam at all points



on the screen. A high-bandwidth 200 MHz amplifier affords maximum image fidelity while digitally-adjusted focus and astigmatism tracking provide crisp, stable displays, even in the corners. To improve viewability, a contrast enhancement panel is bonded to the CRT faceplate.

The frame buffer incorporates ultra fast circuits that allow the user to update the display as fast as 0.2 seconds. This frame buffer has a

storage capacity of 2048 x 2048 x 8 and, by scrolling the entire image can be displayed on the screen.

The T16 bus interface is a 16-bit parallel digital interface for connecting to host busses through a 50-pin connector. The entire display is packaged in a rugged impact resistant cabinet.

Tektronix
COMMITTED TO EXCELLENCE

Standard Performance Characteristics

Display Characteristics

Addressable Area

356 by 267 mm (14 x 10.5 in.)

Addressable Resolution

2048 x 1536 pixels at 60 Hz,
non-interlaced

Aspect Ratio

3:4-Horizontal Long Axis

Spot Size (shrinking raster)

7.5 mils (0.19 mm) center screen
9.0 mils (0.23 mm) corners (maximum)

Brightness

100 cd/m² (30 fL) with installed 60%
contrast enhancement filter

Phosphor

WW (P4) (others available)

Focus

Dynamically controlled, digitally adjusted

Astigmatism

Dynamically controlled, digitally adjusted

Geometric Distortion

Incremental non-linearity: $\pm 3\%$ @25°C

Positional accuracy: $\pm 1\%$ of image
height

Peak-to-peak line variation: $\pm 5\%$

Electrical Characteristics

Frame Buffer Characteristics

Addressable Memory:

2048 x 2048 x 8 bits

Interface: T16 Bus

16-bit asynchronous

20 M bytes/sec, Burst

16 M bytes/sec, Continuous

Driver/Receiver: RS-422 compatible

Cable: 50 conductor flat ribbon cable
with D-connector

Image Update Time: 0.2 seconds

Maximum Connection Distance (GMA 251
to Host):

40 feet (20 M bytes/sec data transfer)

400 feet (2 M bytes/sec data transfer)

Power Requirements

380 watts maximum. Input voltage:

selected by voltage range switch

Range: 87 to 128 volts, 48 to 63 Hz

174 to 256 volts, 48 to 63 Hz

Condition Indicators

Scan fail indicator

Low voltage power supply indicator

High voltage power supply indicator

Environmental Characteristics

Shock

Non-operating: 20 g's, 1/2 sine, 11 ms
duration

Vibration

Non-operating: 15 minutes along each
major axis;

0.010 in. displacement

with frequency varied from 10 Hz to
35 Hz to 10 Hz

Temperature Range

Operating: 0 to 40°C

Non-operating: -40 to +60°C

Humidity

Operating to 95% relative humidity
(non-condensing)

Radiated and Conducted Emissions

Meets FCC Part 15, subpart J, class A

Altitude

Non-operating: 15 Km (50,000 ft)

Operating: 4.5 Km (15,000 ft)

Safety Certification

UL 114/478

CSA 154

DHHS 21 CFR, Subch. J. parts 1020 and
1030

Physical Characteristics

Weight

37.7 Kg (83 lbs)

Dimensions

Height: 429 mm (16.9 in.)

Width: 553 mm (21.8 in.)

Depth: 567 mm (22.3 in.)

Options

Opt. 01: WB (P45) Phosphor with 30%
contrast enhancement filter

Opt. A1: Universal European power cord
220V/16A, 50 Hz operation

Opt. A2: United Kingdom power cord
240V/13A, 50 Hz operation

Opt. A3: Australian power cord 240V/15A,
60 Hz operation

Opt. A4: North American power cord
240V/15A, 60 Hz operation

Opt. A5: Swiss power cord 220V/6A, 50 Hz
operation

Opt. B1: Service Manual

For further information, contact:

U.S.A., Asia, Australia, Central & South America, Japan

Tektronix, Inc.
Beaverton, OR 97077
Phone: (503) 627-7111
Telex: 151754
Fax: (503) 627-5139

France and Africa

Tektronix S.A.
Z.I. Courtaboeuf, Av. du Canada
BP. 13
91941 Les Ulis Cedex
France
Phone: 33 (169) 86 81 81
Telex: (842) 690332 TEKOR A
Fax: 33 (169) 07 09 37

Federal Republic of Germany

Tektronix GmbH
P.O. Box 101544
D-5000 Cologne 1
Phone: 49 (221) 77220
Telex: (841) 8885417 ATEK D
Fax: 49 (221) 7722-362

United Kingdom

Tektronix U.K. Limited
Fourth Avenue
Globe Park
Marlow
Bucks SL7 1YD
Phone: 44 (6284) 6000
Telex: (851) 847277, 847378
Fax: 44 (6284) 74799

North Europe Area

Tektronix Europe B.V.
P.O. Box 406
2130 AK Hoofddorp
The Netherlands
Phone: 31 (2503) 65265
Telex: (844) 74876 TEKE NL
Fax: 31 (2503) 30424

South Europe Area

Tektronix International A.G.
P.O. Box 2142
CH-6300 Zug 2
Switzerland
Phone: 41 (42) 219192
Telex: (845) 868808 TEKZ CH
Fax: 41 (42) 217784

Eastern Europe and the Middle East

Tektronix Ges.m.b.H.
Doerenkampgasse 7
A-1100 Vienna
Austria
Phone: 43 (222) 68 66 02 0
Telex: (847) 111481 TEK A
Fax: 43 (222) 68 66 00

Canada

Tektronix Canada Inc.
P.O. Box 6500
Barrie, Ontario L4M 4V3
Phone: (705) 737-2700
Telex: 06875672 TEKTRONIX BAR
Fax: (705) 737-5588

Tektronix Distributors to serve you around the world:

Argentina, Australia, Austria, Belgium, Bolivia, Brazil,
Canada, Chile, Colombia, Costa Rica, Denmark, East
Africa, Ecuador, Egypt, El Salvador, Federal Republic of
Germany, Finland, France, Greece, Hong Kong, Iceland,
India, Indonesia, Iraq, Israel, Italy, Ivory Coast, Japan,
Jordan, Korea, Kuwait, Lebanon, Malaysia, Mexico,
Morocco, The Netherlands, New Zealand, Norway,
Pakistan, Panama, Peru, Philippines, Portugal, Republic
of South Africa, Saudi Arabia, Singapore, Spain, Sri
Lanka, Sudan, Surinam, Sweden, Switzerland, Syria,
Taiwan, Thailand, Turkey, Tunisia, United Kingdom,
Uruguay, Venezuela, Zambia.

Copyright © 1988, Tektronix, Inc. All rights reserved.
Printed in U.S.A. Tektronix products are covered by U.S.
and foreign patents, issued and pending. Information in this
publication supersedes that in all previously published
material. Specification and price change privileges reserved.
TEKTRONIX and TEK are registered trademarks. For further
information, contact: Tektronix, Inc., P.O. Box 500,
Beaverton, OR 97077 Phone: (503) 627-7111;
TWX (910) 467-8708; TLX 151754; Cable TEKWSGT
Subsidiaries and distributors worldwide

Tektronix
COMMITTED TO EXCELLENCE

Contact your local Tektronix service representative for additional information on Tektronix Service Agreements.

Some of the products, options and services mentioned herein may not be available outside the U.S.A. Contact your local Tektronix representative for details.